



WOYR8.E121922 - Switches, Appliance and Special Use Certified for Canada - Component

Switches, Appliance and Special Use Certified for Canada - Component























See General Information for Switches, Appliance and Special Use Certified for Canada - Component

E-SWITCH INC, DBA LAMB INDUSTRIES
 7153 NORTHLAND DR N.
 BROOKLYN PARK, MN 55428 USA
 Investigated to CAN/CSA-C22.2 No. 61058-1

E121922

Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Pol/ Thr/ Cir	Endurance		Dis IP	Dis (mm)	SPCA	Std. Ed.
							30C cycle	55C cycle				
Micro												
WS08501 f/b 00, f/b P												
	R	0-10	125-250	50-60	25T85	1/2-1.2	6K	10K	67	micro	1A, 1B	2013-02-15
	R	0-2	12	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-0.5	42	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-1	24	DC	25T85	1/2-1.2	6K	10K	67			
WS08501 f/b 00, fb S												
	R	0-10	125-250	50-60	25T85	1/2-1.2	6K	10K	67	micro	1A, 1B	2013-02-15
	R	0-2	12	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-0.5	42	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-1	24	DC	25T85	1/2-1.2	6K	10K	67			
WS08501 f/b 00, fb W												
	R	0-10	125-250	50-60	25T85	1/2-1.2	6K	10K	67	micro	1A, 1B	2013-02-15
	R	0-2	12	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-0.5	42	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-1	24	DC	25T85	1/2-1.2	6K	10K	67			
WS08501 f/b 01, f/b P												

	R	0-10	125-250	50-60	25T85	1/2-1.2	6K	10K	67	micro	1A, 1B	2013-02-15
	R	0-2	12	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-0.5	42	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-1	24	DC	25T85	1/2-1.2	6K	10K	67			
WS08501 f/b 01, f/b S												
	R	0-10	125-250	50-60	25T85	1/2-1.2	6K	10K	67	micro	1A, 1B	2013-02-15
	R	0-2	12	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-0.5	42	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-1	24	DC	25T85	1/2-1.2	6K	10K	67			
WS08501 f/b 01, f/b W												
	R	0-10	125-250	50-60	25T85	1/2-1.2	6K	10K	67	micro	1A, 1B	2013-02-15
	R	0-2	12	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-0.5	42	DC	25T85	1/2-1.2	6K	10K	67			
	R	0-1	24	DC	25T85	1/2-1.2	6K	10K	67			
Rocker Switch												
RBW2A	GP	16(16)	125	50	T85/55	2/1-1.3	6K	50K	--	full 2	A, B, C, D	-
	hp	1/3	125	50	T85/55	2/1-1.3	6K	50K	--			
RBW2A Illuminated												
	GP	16(16)	125	50	T85/55	2/1-1.3	6K	50K	--	full	2, A, B, C, D	-
	hp	1/3	125	50	T85/55	2/1-1.3	6K	50K	--			
RBW2B	hp	1/3	125	50	T85/55	2/2-1.3	6K	50K	--	full 2	A, B, C, D	-
	GP	16(16)	125	50	T85/55	2/2-1.3	6K	50K	--			

Marking: Company name or trademark                      , catalog, model or part number, electrical ratings and the Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Investigated to CSA-C22.2 No. 55

Cat. No.	Amps	Volts	Hz	Load	Endur- ance	Temp C	POL/ THR	Per Pole/ Circuit Code	SPCOA
100 f/b 3P or SP, f/b 1, 2, 3, 4 or 5. 100 f/b 4P or DP f/b 1, 2, 3, 4, 5 or 6									
	2	250	60	R	6K	130	M/M	-/-	-
	5	125	60	R	6K				
100A f/b WSP1 thru WSP5, WDP1 thru WDP6, f/b T1 or T2, f/b B1 or B4, f/b M1, M2, M6, M7, VS2, VS3, f/b Q or R, f/b E, f/b H									

	5	120	60	R	6K	65	M/M	-/A, B	-
	2	250	60	R	6K				
100A f/b WSP1, WSP2, WSP3, WSP4, WSP5, WDP1, WDP2, WDP3, WDP4, WDP5, f/b T1 or T2, f/b B1 or B4, f/b M1, M2, M5, M6, M7, VS2, VS3, M61, M64, M71, VS21, VS31, f/b Q, f/b E									
	2	250	60	R	6K	65	M/M	PP/-	-
	5	125	60	R	6K				
200A f/b WMSP1 thru WMSP6, WMDP1 thru WMDP3, f/b T1 or T2, f/b A1 or A2, f/b M2, M6, M61, M7, VS2, f/b Q or R, f/b E									
	3	120	60	R	6K	65	M/M	-/-	-
	1.5	250	60	R	6K				
200A f/b WMSP1, WMSP2, WMSP3, WMSP4, WMSP5, WMSP6, WMDP1, WMDP2, WMDP3, f/b T1 or T2, f/b A1, f/b M2, M6, M61, M7 or VS2, f/b Q, f/b E f/b 200B, f/b WMSP1, f/b T2 or A1, f/b S, f/b M6, f/b Q, f/b E									
	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
200B f/b WMSP3 thru WMSP5, f/b T2, f/b A1, f/b SM6, f/b Q or R, f/b E									
	3	120	60	R	6K	65	M/M	-/-	-
	1.5	250	60	R	6K				
200MSP f/b 1, 2, 3, 4, 5 or 6. 200 MDP f/b 1, 2, or 3									
	1	250	60	R	6K	130	M/M	-/-	-
	3	120	60	R	6K				
300 f/b 3P, f/b 1, 2, 3, 4 or 5. 300 f/b 4P or DP f/b 1, 2, 3, 4, 5 or 6									
	2	250	60	R	6K	60	M/M	-/-	-
	5	125	60	R	6K				
300A f/b WSP, WDP, W3P, f/b 1 thru 6, f/b R1, R2, R11, R16, J1, J2, J3, J4, J4, J5, J6, f/b 3 letters, f/b M1, M2, M3, M6, M7, VS2, VS3, V2N									
	5	120	60	R	6K	65	M/M	-/A, B	-
	2	250	60	R	6K				
400A f/b WMSP1 thru WMSP5, WMDP1 thru WMDP3, f/b R1, f/b BLK, RED, WHT, f/b M1, M2, M6, M61, M7, M71, VS2, VS21, f/b Q or R, f/b E									
	3	120	60	R	6K	65	M/M	-/-	-
	1.5	250	60	R	6K				
400A f/b WMSP1, WMSP2, WMSP3, WMSP4, WMSP5, WMSP6, WMDP1, WMDP2, WMDP3, f/b R1 f/b M1, M2, M6, M7 or VS2, f/b Q, f/b E f/b 400B, f/b WMSP1, f/b R1, f/b MT or MZ									
	1.5	250	60	R	6K	65	M/M	-/-	-

	3	120	60	R	6K				
400B f/b WMSP1 thru WMSP5, f/b R2, f/b BLK, f/b SM6, f/b Q or R, f/b E									
	3	120	60	R	6K	65	M/M	-/-	-
	1.5	250	60	R	6K				
400MSP f/b 1, 2, 3, 4, 5 or 6. 400 MDP f/b 1, 2 or 3									
	1	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
500 f/b SDP or SSP f/b 1, 2 or 3									
	2	250	60	R	6K	65	1/M	-/-	-
	5	125	60	R	6K				
500A f/b SSP f/b 1 or 3	2	250	60	R	6K	65	2/M	-/-	-
	5	125	60	R	6K				
700A f/b SP7 or DP7, f/b B10 or B21, f/b M1 or M2 or M6 or M7 or VS2 or VS3, f/b Q or R, f/b E, f/b H									
	3	120	60	R	6K	65	M/M	-/-	-
	1	250	60	R	6K				
700SP7, 700DP7	1	250	60	R	6K	65	1/2	-/-	-
	3	120	60	R	6K				
800A f/b WSP8 or WSP9, f/b M2, M6, M61, M7, or VS2, f/b Q, f/b E, may be f/b C1 or C2, f/b BLK, WHT, RED, or GRN									
	3	120	60	R	6K	65	1/M	-/A	-
	1	250	60	R	6K				
800SP9, 800SP8	1	250	60	R	6K	75	1/1	-/-	-
	3	120	60	R	6K				
D16 Series	0.2	250	DC	-	6K	95	M/2	PP/-	-
	6	24	DC	-	6K				
	8	125	60	GP	6K				
	5	250	60	GP	6K				
KO 113A, KO 113B, KO 113C	4	120	60	GP	6K	55	1/1	-/-	-
	2	250	60	GP	6K				
KO 113D	4	120	60	GP	6K	55	1/1	-/-	-
	2	250	60	GP	6K				
KO 128 f/b A, B, C, E, F, G, H									

	4	125	60	GP	6K	55	1/1	-/-	-
	2	250	60	GP	6K				
KO 129, KO 130	4	125	60	GP	6K	105	M/M	PP/-	-
	4	28	DC	-	6K				
	2	250	60	GP	6K				
LA f/b S, K, or P, f/b EE, OA, or PL, f/b U1, V1, f/b 0, 1, 2, 3, or 4, f/b 0, A, B, C, F, G, H, J, or K, f/b RED, GRN, BLU, WHT, ORG, or YEL									
	0.2	250	DC	-	6K	55	M/M	PP/-	-
	6	24	DC	-	6K				
	8	125	60	GP	6K				
	5	250	60	GP	6K				
LS f/b -00 thru -99, f/b C1, C2									
	15	125	60	R	10K	85	1/1	-/-	Note 5
	15	250	60	R	10K				
MDP-16 f/b numbers or letters.									
	8	125	60	GP	6K	55	1/1	-/-	-
	5	250	60	GP	6K				
MS Series	5	125	60	GP	10K	75	1/2	-/-	Note 5
	5	250	60	GP	10K				
PB1973 f/b A, B, C, D, E, F, G, or H									
	15	125	60	GP	6K	105	M/1	PP/-	Notes 7, 8
	15	250	60	GP	6K				
R1966 or R19A	6	250	60	GP	6K	65	1/M	PP/-	3
	15	125	60	GP	6K				
	8	250	60	GP	6K				
R1973 f/b A, B or R9, f/b D, 1, 9 or Y									
	6	250	60	GP	6K	65	1/1	-/-	2, Note 2
	5	227	60	GP	6K				
	9	125	60	GP	6K				
R3070 or R30	15	125	60	GP	6K	65	1/1	-/-	2, 3, Note 1
	10	250	60	GP	6K				

R4 f/b A,C,E,F, or H; f/b BLK, WHT, or GRY; f/b BLK, WHT, RED, RIL, GIL, or YIL; f/b Letters or Numbers; f/b F; f/b 0									
	20	125	60	3/4hp	6K	65	1/M	-/-	3
	16	250	60	1hp	6K				
R4, R5 f/b A, B, C, E, F, H									
	20	125	60	GP	6K	65	M/M	-/-	-
	15	250	60	GP	6K				
R4, R5 f/b D, G or I	15	125	60	GP	6K	65	M/M	-/-	-
	10	250	60	GP	6K				
R5 f/b A,B,C,E,F, or H; f/b BLK, or WHT; f/b BLK, WHT, RED, YEL, GRN, GRY, or ORG; f/b Letters or Numbers; f/b F, f/b 0,1,2, or 3									
	20	125	60	3/4hp	6K	65	M/M	-/-	2, 3
	16	250	60	1hp	6K				
R6 f/b 12 or A	10	125	60	GP	6K	65	M/1	-/-	-
	6	250	60	GP	6K				
RP3508 f/b A or B, may be f/b L									
	3	125	60	GP	6K	85	1/1	-/-	Note 6
	1.5	250	60	GP	6K				
RR3112 f/b A, B, BW, C, D, L or LP, f/b 01 or 02									
	16	125	60	GP	6K	85	1/M	-/-	Note 1, 4
	10	250	60	GP	6K				
RR3130 f/b A, B or C	10	125-250	60	GP	6K	65	2/M	PP/-	2
	6	125-250	60	GP	6K				
RR3402 f/b A, C or D	6	125	60	GP	6K	55	1/M	-/-	-
	3	250	60	GP	6K				
SS f/b 3; f/b -00 thru -99; f/b P1, R1, V1, V2, S1									
	3	125	60	GP	10K	75	1/2	-/-	-
	1.5	250	60	GP	10K				
SS, f/b 075, f/b -00 thru -99, f/b P1, V1 or V2									
	3	125	60	GP	10K	75	1/2	-/A	-
	1.5	250	60	GP	10K				
	0.1	125	60	GP	10K				

	0.1	250	60	GP	10K				
ULV4 f/b F, f/b 2, f/b 3 or B or G or H, f/b N or S or 1, f/b N or S or 1, f/b none or G, f/b none or 2 or 3 or M01, f/b none or 0 or 1 or 2 or 3 or 4 or 5, f/b none or 1 or 3 or 4 or 5 or 6 or 7									
	3	125-250	50/60	R	50K	65	2/2	-/A,B	Note 2
ULV7 f/b F, f/b 2, f/b 3, B, G or H, f/b S or 1, f/b S or 1, f/b none or G, f/b 3, f/b 0, 1, 3, 4 or 5, f/b 1, 3, 4, 5, 6 or 7									
	3	125-250	50/60	R	50K	65	2/2	-/A,B	Note 2
ULV8 fb F, fb 2, f/b 3 or B or G or H, /b S or 1, f/b S or 1, f/b NONE or G, f/b 3, f/b 0 or 1 or 3 or 4 or 5 or 6 or7, f/b 1 or 3 or 4 or 5 or 6 or 7									
	3	125-250	50/60	R	50K	65	2/2	-/A,B	Note 2
WMDP1	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMDP2	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMDP3	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMDP6 may be f/b T1 or T2, f/b A1, f/b M2, M6, M61, M7 or VS2, f/b Q, f/b E, f/b 200B, f/b WMSP1 f/b T2 or A1, f/b SM6, f/b Q, f/b E or may be f/b R1, f/b M1, M2, M6, M7 or VS2, f/b Q, f/b E, /b 400B, f/b WMSP1, f/b R1, f/b MT or MZ									
	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMSP1	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMSP2	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMSP3	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMSP4	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMSP5	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				
WMSP6	1.5	250	60	R	6K	65	M/M	-/-	-
	3	120	60	R	6K				

Note 1 - The suitability of the actuator button material as an enclosure has not been investigated.

Note 2 - Terminations other than solder connections should be evaluated for compliance with the end-use product standard.

Note 3 - This switch has been investigated only for voltage changing and is not intended to be operated under load.











Note 4 - These switches employ a lamp that is powered by a separate DC source. Lamp DC source should be evaluated for compliance with the end-use standard.

Note 5 - The switch was subjected to a minimum 10,000 cycle endurance Test.

Note 6 - These switches may be provided with a light. Lamp life has not been evaluated.

Note 7 - These are lighted switches employing a lamp. The lamp life should be evaluated when required by the end-use product Standard.

Note 8 - Model PB1973 is provided with an additional set of contacts in switch body for illuminate using. The contacts were not tested, and the suitability of the contacts shall be determined in the end-product appliances.

Marking: Company name or trademark , , , , , , , , , catalog, model or part number, electrical ratings and the Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2021-02-10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"